

STAINLESS STEEL % SLOTTED STRUT

Features:

- Manufactured in both type 304 and 316 stainless to meet any stringent sanitary condition
- Polished to a bright, easily maintainable finish that is modern, attractive, easy to clean, and that also enhances the surface's resistance to pitting and bacterial corrosion
- Calbrite stainless steel strut functions in exactly the same way as any other metallic strut
- Channels provided by Calbrite are available in 12 different basic sizes which are subjected to further variation in gauge and depth




- UL 5B Listed
- For installation in accordance with Article 384 of ANSI/NFPA 70. National Electrical Code (NEC)



The Calbrite system of metal framing is based on the use of a continuous slotted channel, and a series of brackets and fittings, which can be fastened to it any point. With Calbrite channel and components, racks, supports for conduit, wiring, and electrical equipment, machine frames, and a limitless variety of structures can be built rapidly, simply and economically.







| Type 304 Part Number | Type 316 Part Number | Size (in) | Width of Hole (in) | Length of Hole (in) | Distance Between Hole (in) | Width of Lip (in) | Sectional Area (in) | Weight per L.F. (lb) |
|-------------------------|-------------------------|--------------|--------------------------|---------------------------|-------------------------------------|----------------------|---------------------------|----------------------------|
| S45810ST78 | S65810ST78 | 1 % x % | 9/16 | 11//8 | 7/8 | 3/8 | 0.285 | 0.970 |

All dimensions are for informational purposes only *Tolerances +/- 5%



