

STAINLESS STEEL THREE-PIECE COUPLINGS

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless threaded conduit
- Machined tapered female threads for smooth bore inside diameter
- No package quantity required





Certifications and Compliances:

- UL/cUL 514B Listed
- UL File # E308159
- CSA C22.2 No. 18.3
- Intended for installation in accordance with ANSI/NFPA 70, National Electrical Code (NEC)
- Intended for installation in accordance with CAN/CSA-C22.1, “Canadian Electrical Code, Part I”

Applications:

To join and connect threaded ends of stainless conduit where neither length of conduit can be turned.



| Part Number | Trade Size (in) | A (in) | B (in) | C (in) | D (in) | E (in) | Female Thread ID (in) | Weight per each (lb) |
|-------------|-----------------|--------|--------|--------|--------|--------|-----------------------|----------------------|
| S605003U00 | ½ | 1.535 | 1.680 | 0.800 | 0.750 | 1.240 | 0.840 | 0.45 |
| S607003U00 | ¾ | 1.800 | 1.750 | 0.825 | 0.770 | 1.300 | 1.050 | 0.60 |
| S610003U00 | 1 | 2.143 | 2.130 | 1.000 | 0.975 | 1.553 | 1.315 | 0.98 |
| S612003U00 | 1¼ | 2.540 | 2.160 | 1.030 | 0.985 | 1.590 | 1.660 | 1.18 |
| S615003U00 | 1½ | 2.870 | 2.161 | 1.030 | 0.985 | 1.600 | 1.900 | 1.50 |
| S620003U00 | 2 | 3.525 | 2.200 | 1.040 | 1.000 | 1.630 | 2.375 | 2.27 |
| S625003U00 | 2½ | 3.400 | 3.720 | 1.580 | 1.560 | 2.950 | 2.875 | 2.50 |
| S630003U00 | 3 | 4.070 | 3.800 | 1.610 | 1.610 | 3.100 | 3.500 | 3.28 |
| S640003U00 | 4 | 5.250 | 4.110 | 1.850 | 1.750 | 3.200 | 4.500 | 6.35 |

All dimensions are for informational purposes only *Tolerances +/- 5%

