

STAINLESS STEEL DROP-IN ANCHOR

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished to a bright, easily maintainable finish that is modern, attractive, easy to clean, and that also enhances the surface's resistance to pitting & bacterial corrosion
- Internally threaded anchor allows easy bolt removability and service work
- Standard NPT threads allow for trouble-free installations
- Shallow embedment depth with high performance
- No package quantity required



For use in structural fastening. Internally threaded, flush-mounted.



Part Number	Anchor Size (in)	Hole Diameter (in)	Embedment (in)	PSI	Tensile Strength	Shear	Thread Depth (in)	Anchor Length (in)	Weight per 100 (lb)
S60200DR00	1/4	1/4	1	4000	2067	2750	1/2	1	2.88
S60300DR00	3/8	3/8	1%6	4000	3995	5169	5/8	1%6	6.32
S60500DR00	1/2	1/2	2	4000	4110	7444	3/4	2	11.56
S60600DR00	5/8	5/8	23/8	4000	5750	12212	1	2%16	34.80
S60700DR00	3/4	3/4	21/2	4000	10807	14223	11/4	3%6	48.00

All dimensions are for informational purposes only *Tolerances +/- 5%



