

STAINLESS STEEL EYS CONDUIT SEALING FITTING

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Explosion proof, dust-ignition proof
- Designed for use with stainless steel threaded conduit
- Machined tapered female threads for smooth bore inside diameter
- Designed for use with vertical and horizontal installations
- Large opening for easy packing and setup of sealing compound and fiber dam
- No package quantity required



Certifications and Compliances:

- UL 1203 Listed
- UL File # E465422
- CSA C22.2 Listed
- Suitable for use in:
Class I, Div. 1 & 2, Groups A, B, C & D
Class II, Div. 1 & 2, Groups E, F & G
Class III Hazardous Locations

Applications:

Calbrite’s stainless steel EYS (Seal-Off) fittings are designed for use in hazardous areas and harsh environments for both horizontal and vertical installations. Used to prevent possible explosions from occurring through conduit systems and igniting outside atmospheres. When properly installed and filled with a UL-listed sealing compound, they create a physical barrier that limits the passage of vapors and gases throughout the conduit system.



Part Number	Trade Size (in)	Overall Length (in)	Overall Width (in)	Overall Height (in)	Sealing Compound Required (oz)	Sm. Plug Hole Opening (in)	Lg. Plug Hole Opening (in)	Weight per each (lb)
S60700EYS0	¾	3.500	1.380	2.100	1¾	0.470	0.920	0.880
S61000EYS0	1	3.760	1.650	2.370	2	0.470	0.920	1.180

All dimensions are for informational purposes only *Tolerances +/- 5%

