

STAINLESS STEEL GROUNDING HUBS

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless • threaded conduit
- Use of neoprene O-ring assures weatherproof seal
- . Includes a type 316 stainless steel locknut for a secure installation
- No package quantity required •


Certifications and Compliances:

- NSF / ANSI 169 Certified
- Made in USA

Applications:

To connect threaded stainless conduit to a threadless opening in a box or enclosure in an outdoor or indoor location. To positively bond conduit to a box or enclosure.

and the second	



Part Number	Trade Size (in)	A (in)	B (in)	Width (in)	Thread Length (in)	Grounding Screw (in)	Weight per each (Ib)
S60500LTV2	1/2	1.666	0.954	1.700	0.639	10-32 x %"	0.390
S60700LTV2	3/4	1.686	0.959	1.931	0.639	10-32 x %"	0.530
S61000LTV2	1	2.040	1.120	2.204	0.795	1⁄4"-20 x 1⁄2"	0.750
S61200LTV2	1 1⁄4	2.084	1.125	2.564	0.795	1⁄4"-20 x 1⁄2"	0.970
S61500LTV2	1 1⁄2	2.084	1.130	2.800	0.795	1⁄4"-20 x 1⁄2"	1.170
S62000LTV2	2	2.110	1.135	3.335	0.795	5⁄16"-18 x ½"	1.650
S62500LTV2	2 1/2	2.985	1.520	3.905	1.175	5⁄16"-18 x ½"	2.250
S63000LTV2	3	3.045	1.525	4.600	1.175	5⁄16"-18 x ½"	3.000
S64000LTV2	4	3.150	1.530	5.600	1.175	5⁄16"-18 x ½"	4.860

All dimensions are for informational purposes only *Tolerances +/- 5%



