

STAINLESS STEEL BOX CONNECTORS

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Machined tapered male threads by machined smooth bore inside diameter
- No package qty. required

Applications:

Used to connect a box or enclosure to the conduit coupling. It can also be used with a locknut to connect two boxes side by side, or back to back and with a locknut to connect fixture housings in continuous runs.

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Pharmaceuticals & Cosmetics

Refining & Extraction Sites

- Pulp & Paper Mills
- Marine & Coastal Facilities

- Chemical Plants
- Water & Wastewater Treatment
- Petrochemical

Part Number	Trade Size (in)	Inner Diameter (in)	Width (in)	Legth (in)	Hex Nut Thickness (in)	Thread Length (in)	Weight (ea) per (lb)
S60500CH00	1⁄2	0.650	1.140	1.000	0.210	0.625	0.090
S60700CH00	3/4	0.830	1.410	1.000	0.210	0.690	0.120
S61000CH00	1	1.140	1.720	1.290	0.275	0.900	0.150
S61200CH00	1 1⁄4	1.390	2.070	1.320	0.340	0.940	0.280
S61500CH00	1 1⁄2	1.625	2.320	1.410	0.425	0.940	0.390
S62000CH00	2	2.000	2.830	1.420	0.440	0.940	0.590
S62500CH00	2 1⁄2	2.450	3.400	1.920	0.450	1.380	0.980
S63000CH00	3	3.000	3.850	1.580	0.500	1.380	1.310
S64000CH00	4	3.970	5.120	2.000	0.500	1.440	1.570

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit atkore.com/calbrite 🌐

©2020 Atkore International, Inc. All rights reserved. CLB-SUB-5070-2006

