

# Stainless Steel EMT Split Ring Clamps

## Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished to a bright, easily maintainable finish that is modern, attractive, easy to clean, and that also enhances the surface's resistance to pitting and bacterial corrosion
- Designed for use with stainless steel EMT
- Two type 316 stainless steel bolts included
- No package quantity required



## Applications:

Calbrite's stainless steel Split Ring Clamps are designed for mounting and securing conduit, horizontally or vertically, away from the wall or device in wash-down or corrosive environments when used with Calbrite's Mounting Plates and Extensions.

Part Number	Trade Size (in)	Height (in)	Length (in)	Width (in)	Female Thread	Bolt Size (in)	Thickness (in)	Weight per EA (lb)
S20500SP00	½	1.13	2.09	0.53	¾	10-24 x 5/8	0.13	0.11
S20700SP00	¾	1.42	2.32	0.55	¾	10-24 x 5/8	0.13	0.13
S21000SP00	1	1.68	2.58	0.55	¾	10-24 x 5/8	0.14	0.15
S21200SP00	1 ¼	2.04	3.08	0.57	¾	10-24 x 5/8	0.14	0.20
S21500SP00	1 ½	2.41	3.34	0.59	¾	10-24 x 5/8	0.15	0.24
S22000SP00	2	2.90	3.80	0.61	¾	10-24 x 5/8	0.15	0.29