

STAINLESS STEEL WEDGE ANCHORS

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Chamfered threaded end for ease of starting nut
- Available in a wide range of diameters and lengths
- No package quantity required



Applications:

Calbrite's stainless steel Wedge Anchors are fully threaded and torque-controlled. They are suitable for corrosive applications and multiple applications, including solid concrete and grout-filled concrete masonry.

Part Number	Wedge / Drill Bit Size (in)	Length (in)	Min. Fixture Hole (in)	Wrench Size (in)	Concrete Installation Torque (ft.-lbf.)	Weight per each (lb)
S60200WR17	1/4	1 3/4	5/16	7/16	8	0.03
S60200WR22	1/4	2 1/4	5/16	7/16	8	0.03
S60200WR32	1/4	3 1/4	5/16	7/16	8	0.04
S60300WR27	3/8	2 3/4	7/16	9/16	30	0.09
S60300WR30	3/8	3	7/16	9/16	30	0.10
S60300WR35	3/8	3 1/2	7/16	9/16	30	0.12
S60300WR37	3/8	3 3/4	7/16	9/16	30	0.12
S60500WR42	1/2	4 1/4	9/16	3/4	60	0.24

All dimensions are for informational purposes only *Tolerances +/- 5%

