

Galvanized Rigid Conduit (GRC) 90° Elbows

Features:

- Hot-dip galvanized for excellent corrosion resistance
- High strength ductile steel for long life and easy bending
- Smooth, continuous raceways for fast wire-pulling
- Kwik-Release End Cap to protect threads
- Listed to Safety Standard UL 6
- Manufactured in accordance with ANSI C80.1
- Available in trade sizes 1/2" (16 mm) - 6" (155 mm)

Standards:

- Precision manufacturers for dependable, long-lasting value and ultimate protection for electrical conductors
- Highly resistant to damage from impact (Article 344 NEC)
- Recognized as equipment grounding conductor (Sec 250.118 NEC)
- UL Safety Standard 6



Galvanized Rigid Conduit (GRC) 90° Elbows

Listed to Safety Standard UL 6

Manufactured in accordance with ANSI C80.1



Trade Size	Metric Designator	Radius (A) ¹		Offset (B) ²		Straight (D) ¹		Approximate Weight Per 100 Pieces		Standard Package
		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb)	(kg)	
1/2	16	4	102	5 ⁷ / ₈	149	1 ¹ / ₂	38	68	30.8	50
3/4	21	4 ¹ / ₂	114	7	178	1 ¹ / ₂	38	109	49.4	50
1	27	5 ³ / ₄	146	8 ³ / ₄	222	1 ⁷ / ₈	48	201	91.2	25
1 ¹ / ₄	35	7 ¹ / ₄	184	10 ³ / ₄	273	2	51	336	152.4	20
1 ¹ / ₂	41	8 ¹ / ₄	210	12 ¹ / ₄	311	2	51	460	208.7	15
2	53	9 ¹ / ₂	241	14 ¹ / ₂	368	2	51	729	330.7	10
2 ¹ / ₂	63	10 ¹ / ₂	267	17	432	3	76	1374	623.2	1
3	78	13	330	19 ⁵ / ₈	498	3 ¹ / ₈	79	2045	927.6	1
3 ¹ / ₂	91	15	381	22 ³ / ₄	578	3 ¹ / ₄	83	2860	1297.3	1
4	103	16	406	23 ⁷ / ₈	606	3 ³ / ₈	86	3519	1596.2	1
5	129	24	610	34 ⁷ / ₈	886	3 ⁵ / ₈	92	6942	3148.9	1
6	155	30	762	45 ¹ / ₂	1156	3 ³ / ₄	95	11960	5425.1	1

¹Minimum requirement as per UL Standard

²For information only, not a requirement as per UL Standard

Sizes 2¹/₂" (63 mm) and larger shipped in palletized bulk cartons

Also available in the following Degrees (60°, 45°, 30°, 22¹/₂°, 15° & 11¹/₄°)

