



**CONDEX**

# MANDRELS



FISHING & RODDING

## Short Rubber Slug

For proving duct integrity and for spreading cable pulling lubricant especially in tight-radius bends. 4,500 lbs. (20,016 N) load capacity.

Part Number	Duct Size (in)	Body Length		Max O.D.	
		(in)	(mm)	(in)	(mm)
08082020	2	3.25	83	2.00	51
08082025	2½	3.25	83	2.50	64
08082030	3	3.25	83	3.00	76
08082035	3½	3.25	83	3.50	89
08082040	4	3.25	83	4.00	102
08082050	5	3.25	83	5.00	127
08082060	6	3.25	83	6.00	154
08082080	8	3.25	83	8.00	203



## Wire Brush Mandrel

Flat steel bristles with a pulling eye on one end and a loop on the other end. Easily removes sand, grit and other light obstructions from the duct. 800 lbs. (3,558 N) load capacity.

Part Number	Duct Size (in)	Body Length		Overall Length		Max O.D.	
		(in)	(mm)	(in)	(mm)	(in)	(mm)
08028904	1¼	4.25	108	7.50	191	1.00	25
08028905	1½	4.25	108	7.50	191	1.25	32
08028900	2	4.25	108	9.16	232	1.75	44
08046000	2½	4.25	108	9.16	232	2.25	57
08067100	3	5.50	140	9.16	232	2.75	70
08067200	3½	5.00	127	9.16	232	3.25	82
08029000	4	6.75	171	9.16	232	3.75	95
08029100	5	6.50	165	9.16	232	4.75	121
08068100	6	6.75	171	9.16	232	5.75	146
08029080	8	4.75	121	9.73	247	7.75	197



08028904 & 08028905



## Heavy Duty Wire Brush Mandrels

Heavy-duty steel bristles with pulling eyes on each end. For removing obstructions from the duct.

Part Number	Duct Size (in)	Body Length		Max O.D.		Load	
		(in)	(mm)	(in)	(mm)	(lbs)	(N)
08900546	2	3.5	89	1.75	44	1,240	5,516
08900547	2½	4.25	108	2.25	57	1,240	5,516
08900548	3	5.25	133	2.75	70	1,240	5,516
08900549	3½	5.25	133	3.25	82	2,240	9,964
08900550	4	5.25	133	3.75	95	2,240	9,964
08900551	5	5.00	123	4.75	121	2,240	9,964
08900552	6	5.00	123	5.75	146	2,240	9,964
08900553	8	5.00	123	7.75	196	2,240	9,964



## Flexible Steel Mandrel

Steel discs in graduated sizes make this mandrel ideal for removing obstructions in duct with extreme bends. 7,000 lbs. (31,136 N) load capacity.

Part Number	Duct Size (in)	Body Length		Max O.D.	
		(in)	(mm)	(in)	(mm)
08021700	2*	7.31	186	1.75	44
08021925	2½	11.25	286	2.25	57
08021800	3	11.25	286	2.75	70
08049400	3½	11.25	286	3.25	83
08067400	4 Sch 80	11.25	286	3.50	89
08021900	4	11.25	286	3.75	95
08067500	5 Sch 80	11.25	286	4.25	108
08058900	5	11.25	286	4.75	121
08067600	6 Sch 80	11.25	286	5.50	140
08059000	6	11.25	286	5.75	146
08079500	8	11.25	286	7.75	197

\*2,000 lbs. (8,896 N) load capacity.

**!** When using the flexible steel mandrel there is the potential for duct shaving to occur.

