



JAMB SKID



Jamb Skid

The Condux Jamb Skid is a device for supporting sheaves or quadrant blocks inside a manhole to pull cable into underground conduit.

Constructed of solid aluminum, the Jamb Skid is both strong and lightweight. In most instances, it can be installed by one person. The complete unit is created by combining a base unit with one of several extension units, depending upon the height required. Locking 1 1/4" (32 mm) pins, allow the height adjustment of the Jamb Skid. Also, the width adjusts from 7" (178 mm) to 11" (279 mm) to accept all Condux sheave assemblies up to 8" (203 mm). 10,000 lbs. (44,480 N) cable tension load rated.

NOTE: Order base section, extension, and sheave separately for a complete Jamb Skid unit. Sheave pin and locking pins are included with the base section.

Part Number	Description	Manhole Height Range	
		(in)	(m)
08097000	58" (1.17 m) (Base Section)		
08097001	43" (1.09 m) Extension	63-80	1.24 - 2.03
08097002	76" (1.93 m) Extension	78-109	1.98 - 2.77
08097003	109" (2.8 m) Extension	107-138	2.72 - 3.51

Replacement Pins

Part Number	Description
08097040	1 1/4" (32 mm) diameter sheave pin
08097060	Locking Pin Kit (includes two locking pins)

Sheaves

Refer to the chart on page 75 for specifications on sheave products for use with the Condux Jamb Skid.

20,000 lbs. Jamb Skid

Constructed of steel and rated for 20,000 lbs (88,964 N) cable tension. Base section includes sheave pin and locking pins.

Part Number	Description
08097509	Base Section
08097532	43" (1.09 m) Extension
08097529	76" (1.93 m) Extension
08097508	109" (2.8 m) Extension

Sheaves for 20,000 lbs. Jamb Skid

Part Number	Sheave Size
08097504	8 x 11 in (203 x 279 mm)

