

Carriers

Part Number	Description	Carrier OD
08202020	Carrier, Winch Line 2" SCH40&80, TC6	2.05" (53 mm)
08202520	Carrier, Winch Line 2.5" SCH40&80	2.50" (64 mm)
08202920	Carrier, Winch Line 3" SCH 40&80	3.13" (80 mm)
08203020	Carrier, Winch Line 3" SCH40, TC6&8	3.50" (89 mm)
08203420	Carrier, Winch Line 3.5" SCH 40&80	3.75" (95 mm)
08203520	Carrier, Winch Line 3.5" TC6&8	4.00" (102 mm)
08203920	Carrier, Winch Line 4" SCH40&80, TEL	4.25" (108 mm)
08204020	Carrier, Winch Line 4" SCH40,TEL	4.50" (114 mm)
08204920	Carrier, Winch Line 5" SCH 40&80	5.25" (133 mm)
08205020	Carrier, Winch Line 5" SCH40, TC6&8	5.50" (140 mm)
08205920	Carrier, Winch Line 6" SCH 40&80	6.25" (159 mm)
08206020	Carrier, Winch Line 6" SCH40, TC6&8	6.50" (165 mm)

Alternate carrier options available on pages 16-17. See: Line Carriers, Cable Chute Line Carriers and Duct Projectiles.

! Not for use in steel conduit.



Rope Adapter

Rope Adapter

08201091



Storage Case

Storage Case

08201093



Poly Line Pail

Line attaches to the back of a foam carrier, inflatable carrier or line carrier and is used to pull back a rope. Packaged in a weather-proof, reusable plastic bucket with lid.

Part Number	Break Strength (lbs)	Break Strength (N)	Length (ft)	Length (m)
08561285*	200	890	6,500	1,981
08561297*	450	2,002	2,500	762

*Pallet quantities of 48 available.



Poly Line Replacement String

Replacement string refills.

Part Number	Break Strength (lbs)	Break Strength (N)	Length (ft)	Length (m)
08561284*	200	890	6,500	1,981
08561299*	450	2,002	2,500	762

*Pallet quantities of 80 available.

Polyester Woven Pre-Lubed Tape

Recommended pulling tape for fiber optic and coaxial cable pulling. Pre-lubricated tape provides a low coefficient of friction for easier cable pulling. Flat design distributes the side-wall load and reduces duct burn-through. Marked with accurate sequential footage markings.

Part Number	Break Strength (lbs)	Break Strength (N)	Approx Width (in)	Approx Width (mm)	Length (ft)	Length (m)
08075003	1,250	5,560	1/2	13	3,000	915
08075103	1,800	8,006	5/8	16	3,000	915
08096303	2,500	11,120	3/4	19	3,000	915

