



CABLE GUIDE ACCESSORIES



POWER CABLE INSTALLATION

Aluminum Split Bells


Plugs into conduit in manhole wall, guiding cable safely into the conduit regardless of the pulling angle.

| Part Number | Size | | Tube Length | | Tube I.D. | | Tube O.D. | |
|-------------|-------|------|-------------|------|-----------|------|-----------|------|
| | (IN.) | (MM) | (IN.) | (MM) | (IN.) | (MM) | (IN.) | (MM) |
| 08041520 | 2 | 51 | 8 | 203 | 1.625 | 41 | 1.875 | 48 |
| 08041530 | 3 | 76 | 8 | 203 | 2.625 | 67 | 2.875 | 73 |
| 08041540 | 4 | 102 | 8 | 203 | 3.625 | 92 | 3.875 | 98 |
| 08041550 | 5 | 127 | 8 | 203 | 4.625 | 117 | 4.875 | 124 |
| 08041560 | 6 | 152 | 8 | 203 | 5.625 | 143 | 5.875 | 149 |
| 08041564 | 6 | 152 | 12 | 305 | 5.625 | 143 | 5.875 | 149 |
| 08041570 | 8 | 203 | 12 | 305 | 7.500 | 191 | 7.875 | 200 |



Replacement Sheaves

Refer to this chart for specifications on sheave sizes for these products: 4,000 lb. (17,793 N) Hooked Hanger Sheaves, Cable Feeding Sheaves, Corner Cable Guides, Heavy Duty Quadrant Blocks, Three Sheave Cable Guides, and Jamb Skid.



Sheaves Specifications

| Part Number | Nylatron Part Number | Sheave Size | | Maximum Cable O.D. (A) | | Min. Bending Radius (B) | | Max. Sheave Width (C) | | Maximum Sheave O.D. (D) | | Shaft Diameter (E) | |
|-------------|----------------------|-------------|-----------|------------------------|------|-------------------------|------|-----------------------|------|-------------------------|------|--------------------|------|
| | | (IN.) | (MM) | (IN.) | (MM) | (IN.) | (MM) | (IN.) | (MM) | (IN.) | (MM) | (IN.) | (MM) |
| 08539308 | 08539304 | 1 x 3 | 25 x 76 | 1.50 | 38 | 0.75 | 19 | 3.19 | 81 | 3.00 | 76 | 0.63 | 16 |
| 08539136 | 08539137 | 4 x 7 | 102 x 178 | 4.00 | 102 | 2.25 | 57 | 4.35 | 110 | 7.00 | 178 | 1.25 | 32 |
| 08539236 | 08539237 | 5 x 7 | 127 x 178 | 5.00 | 127 | 2.25 | 57 | 4.93 | 125 | 7.00 | 178 | 1.25 | 32 |
| 08046711 | 08046712 | 4 x 11 | 102 x 279 | 4.00 | 102 | 3.75 | 95 | 4.94 | 125 | 11.00 | 279 | 1.25 | 32 |
| 08046811 | 08046812 | 5 x 11 | 127 x 279 | 5.00 | 127 | 3.25 | 83 | 5.94 | 151 | 11.00 | 279 | 1.25 | 32 |
| 08087811 | 08087812 | 6 x 11 | 152 x 279 | 6.00 | 152 | 3.13 | 79 | 6.94 | 176 | 11.00 | 279 | 1.25 | 32 |
| 08087911 | 08087912 | 8 x 11 | 203 x 279 | 8.25 | 210 | 2.75 | 70 | 8.94 | 227 | 11.00 | 279 | 1.25 | 32 |

4,000 lb Sheaves

| Part Number | Nylatron Part Number | Sheave Size | | Maximum Cable O.D. (A) | | Min. Bending Radius (B) | | Max. Sheave Width (C) | | Maximum Sheave O.D. (D) | | Shaft Diameter (E) | |
|-------------|----------------------|-------------|-----------|------------------------|------|-------------------------|----|-----------------------|-----|-------------------------|-----|--------------------|------|
| | | (IN.) | (MM) | (IN.) | (MM) | (IN.) | MM | (IN.) | MM | (IN.) | MM | (IN.) | (MM) |
| 08042612 | 08046812 | 5 x 11 | 127 x 279 | 5.00 | 127 | 3.25 | 83 | 5.94 | 151 | 11.00 | 279 | 1.25 | 32 |

NOTE: Nylatron® is a registered trademark of DSM.