



PE & PVC PULLING EYES

PE & PVC Pulling Eyes

The Condux PE & PVC Pulling Eyes feature two designs to suit your needs.

The non-sleeved design provides optimum gripping power, an extremely rigid center rod to prevent bending, and a steel tapered lead cone with the same O.D. as the conduit. The sleeved versions are water tight eyes that feature a multiple O-Ring configuration. These also have an extremely rigid center rod and sleeves designed to protect the outer leading edge of the conduit to form a water tight seal. Both the sleeved and non-sleeved designs feature split gripping segments with aggressive gripping threads, coupled with a steel expansion plug that grips the full range of conduit I.D.s.

Installation of the PE & PVC Pulling Eyes simply requires the leading eye to be tightened. The pulling eyes come standard with attachment eyes at both ends for connecting rope or steel lines. Pull-out strengths generally exceed the tensile capacity of the conduit.

NOTE: PE & PVC Pulling Eyes come with a 90 day limited warranty.



See chart on page 38 for swivel compatibility.
Replacement O-Rings on page 39.



Non-Sleeved Pulling Eye
(page 36)



Short-Sleeved Pulling Eye
(page 37)

PE & PVC Pulling Eyes Non-Sleeved Part Numbers

Part Number	Nominal Size (IN.)	Length		Conduit ID				Lead Cone OD		Duct Type	Nominal Duct ID	
		(IN.)	(MM)	Minimum		Maximum		(IN.)	(MM)		(IN.)	(MM)
08220220	1.5	8.33	211	1.51	38	1.80	46	2.375	60	1.5 SDR 11.0-17.0	1.53-1.66	39-42
										1.5 SCH 40	1.59	40
										1.5 SIDR	1.61	41
										2.0 SDR 11.0-17.0	1.92-2.08	49-53
08220020	2	8.18	206	1.88	48	2.15	55	2.375	60	2.0 SCH 80	1.91	49
										2.0 SCH 40	2.05	52
										2.0 SIDR	2.07	53
										3.0 SDR 11.0-17.0	2.83-3.06	72-78
08220030	3	11.89	302	2.69	68	3.13	79	4.00	102	3.0 SCH 80	2.83	72
										3.0 SCH 40	3.04	77
										3.0 SIDR	3.07	78
										4.0 SDR 11.0-17.0	3.63-3.94	92-100
08220611	4	14.11	358	3.50	89	4.20	106	4.81	122	4.0 SCH 80	3.79	96
										4.0 SCH 40	4.00	102
										4.0 SIDR	4.03	102
										5.0 SDR 11.0-21.0	4.49-5.03	114-128
08220050	5	18.45	469	4.25	108	5.06	129	5.56	141	5.0 SCH 80	4.77	121
										5.0 SCH 40	5.02	128
										6.0 SDR 11.0-21.0	5.35-5.96	136-151
08220060	6	19.6	498	5.06	129	6.00	152	7.00	178	6.0 SCH 80	5.71	145



PE & PVC PULLING EYES



PE & PVC Pulling Eyes: Short Sleeved Part Numbers

	Nominal Size	Length		Conduit ID				Sleeve ID		Duct Type	Nominal Duct ID	
				Minimum		Maximum						
Short Sleeved Part Number	(IN.)	(IN.)	(MM)	(IN.)	(MM)	(IN.)	(MM)	(IN.)	(MM)		(IN.)	(MM)
08220612	1.0	6.23	158	1.00	25	1.25	32	1.415	36	1.0 SDR 11.0	1.06	27
										1.0 SDR 13.5	1.10	28
08220600	1.25	6.23	158	1.25	32	1.50	38	1.76	48	1.25 SDR 11.0	1.33	34
										1.25 SCH 40	1.34	34
										1.25 SDR 13.5	1.39	35
										1.25 SDR 15.5	1.43	36
										1.25 SDR 17.0	1.44	37
										1.25 SDR 21.0	1.50	38
08220601	1.5	6.23	158	1.50	38	1.75	44	2.01	51	1.50 SDR 11.0	1.53	39
										1.50 SDR 13.5	1.60	41
										1.50 SCH 40	1.59	40
										1.50 SDR 15.5	1.63	41
										1.50 SDR 17.0	1.66	42
										1.50 SDR 21.0	1.72	44
08220602	2.0	8.18	208	1.88	48	2.15	55	2.45	62	2.0 SDR 11.0	1.92	49
										2.0 SDR 13.5	2.00	51
										2.0 SDR 15.5	2.05	52
										2.0 SCH 40	2.05	52
										2.0 SDR 17.0	2.08	53
										2.0 SDR 21.0	2.15	55
08220609	2.5	8.80	224	2.31	59	2.56	65	3.01	76	2.5 SDR 11.0	2.32	59
										2.5 SDR 13.5	2.42	61
										2.5 SCH 40	2.45	62
										2.5 SDR 15.5	2.48	63
										2.5 SDR 17.0	2.52	64
08220603	3	11.89	302	2.69	68	3.13	79	3.63	92	3.0 SDR 11.0	2.83	72
										3.0 SDR 13.5	2.95	75
										3.0 SDR 15.5	3.02	77
										3.0 SDR 17.0	3.06	78
										3.0 SCH 40	3.04	77
08220604	4	14.11	358	3.50	89	4.06	103	4.63	118	4.0 SDR 11.0	3.63	92
										4.0 SDR 13.5	3.79	96
										4.0 SCH 80	3.79	96
										4.0 SDR 15.5	3.89	99
										4.0 SDR 17.0	3.94	100
										4.0 SCH 40	4.00	102
4.0 SDR 21.0	4.05	103										
08220605	5	18.45	469	4.25	108	5.06	129	5.63	143	5.0 SDR 11.0	4.49	114
										5.0 SDR 13.5	4.69	119
										5.0 SDR 15.5	4.80	122
										5.0 SDR 17.0	4.87	124
										5.0 SDR 21.0	5.00	127
										5.0 SCH 40	5.05	128
08220606	6	19.60	498	5.06	129	6.00	152	6.76	172	6.0 SDR 11.0	5.35	136
										6.0 SDR 13.5	5.58	142
										6.0 SDR 15.5	5.72	145
										6.0 SDR 17.0	5.80	147
										6.0 SDR 21.0	5.96	151
08220608	8	21.53	547	6.63	168	7.69	195	8.84	224	8.0 SDR 11.0	6.96	177
										8.0 SDR 13.5	7.27	185
										8.0 SDR 15.5	7.45	189
										8.0 SDR 17.0	7.55	192