## CROSSARM BRACKET - RATCHET STRAP



## **KEY FEATURES**

- Mount on wooden, fibreglass or composite crossarms, and concrete, wood, or steel poles
- Allows stringing blocks to be mounted horizontally or vertically

The ZMI14338 Crossarm Ratchet Strap bracket, used in conduction with Slingco's Stringing Blocks ZAB4004 & ZAB4344 can be mounted on wooden, fibreglass or composite crossarms, as well as concrete, wood, or steel poles. This versatile crossarm bracket ratchet strap allows stringing blocks to be mounted horizontally or vertically. Strap length is 1300mm, with a WLL of 650kg.

Slingco Part No.	Description	SWL (lb)	SWL (kg)
ZMI14338	Crossarm Bracket - Ratchet Strap	2,500	1,133

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

## Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.









