

DOUBLE EYE CLOSED MESH CABLE SUPPORT SOCKS



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed for two connect/support points

Double eye closed mesh support sock in 304 stainless steel. Two eyes for two connect/support points. Closed mesh for when end of cable is available.

| Slingco Part No. | Approx. Break Load (lb) | Approx. Break Load (kg) | Lattice Length (in) | Lattice Length (mm) | Lattice Material | Range (in) | Range (mm) |
|------------------|-------------------------|-------------------------|---------------------|---------------------|------------------|-------------|------------|
| ZCS2038 | 512 | 230 | 9.7 | 247 | 304 Stainless | 0.50 - 0.63 | 12 - 16 |
| ZCS2039 | 740 | 335 | 9.7 | 247 | 304 Stainless | 0.63 - 0.75 | 16 - 19 |
| ZCS2040 | 1,000 | 450 | 13 | 331 | 304 Stainless | 0.75 - 1.00 | 19 - 25 |
| ZCS2041 | 1,540 | 695 | 15 | 344 | 304 Stainless | 1.00 - 1.25 | 25 - 31 |
| ZCS2042 | 1,540 | 695 | 16.5 | 382 | 304 Stainless | 1.25 - 1.50 | 31 - 38 |
| ZCS2043 | 2,010 | 910 | 15 | 420 | 304 Stainless | 1.50 - 1.75 | 38 - 44 |
| ZCS2044 | 3,230 | 1,465 | 21 | 509 | 304 Stainless | 1.75 - 2.00 | 44 - 50 |
| ZCS2045 | 3,230 | 1,465 | 24 | 535 | 304 Stainless | 2.00 - 2.50 | 50 - 63 |
| ZCS2046 | 4,000 | 1,815 | 26 | 611 | 304 Stainless | 2.50 - 3.00 | 63 - 76 |
| ZCS2047 | 5,000 | 1,815 | 29 | 662 | 304 Stainless | 3.00 - 3.50 | 76 - 89 |
| ZCS2048 | 5,000 | 1,815 | 29 | 738 | 304 Stainless | 3.50 - 4.00 | 89 - 102 |
| ZCS6404 | 10,000 | 1,815 | 30 | 762 | 304 Stainless | 4.00 - 4.50 | 102-114 |
| ZCS6405 | 10,000 | 1,815 | 30 | 762 | 304 Stainless | 4.50 - 5.00 | 114-127 |
| ZCS6406 | 10,000 | 1,815 | 30 | 762 | 304 Stainless | 5.00 - 5.50 | 127-140 |

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

GET IN TOUCH

+61 3 8840 6556

sales@slingcoaustralia.com.au

DOUBLE EYE CLOSED MESH CABLE SUPPORT SOCKS

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia **Sales:** +61 3 8840 6556

GET IN TOUCH



+61 3 8840 6556



sales@slingcoaustralia.com.au