

DOUBLE LOCKING SNAP HOOK



KEY FEATURES

- ✓ Double action, self-locking gate mechanism
- ✓ Zinc electroplated for rust resistance
- ✓ Rated to 5,000 lbs.
- ✓ Meets British Standard EN362:2004

Slingco's Double Locking Snap Hook has a safe working load limit of 5,000 lb, with a side opening feature allowing quick access to remove the hand line.

Zinc plated for rust resistance this strong Snap Hook requires double pressure points for opening to ensure safety without allowing accidental opening.

Slingco Part No.	Description	Working Load Limit (lb)	Working Load Limit (kg)
HMI8556	Double Locking Snap Hook	5,000	2,267

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



L9, 1 York Street, Sydney, NSW 2000, Australia Sales: +61 3 8840 6556

GET IN TOUCH



+61 3 8840 6556



sales@slingcoaustralia.com.au