## **ULTRA-FLEX NON-METALLIC PULLING SOCK**



## **KEY FEATURES**

- Non-metallic
- 🔽 Light weight yet strong
- Nylon collar
- Colored tabs for easy identification

Lightweight and strong pulling sock made of non-metallic aramid fibre.

| Part No. | Range (in)  | Range (mm) | Colour Code | Approx. Break Load (lbs.) | Approx. Break Load (kg) |
|----------|-------------|------------|-------------|---------------------------|-------------------------|
| ZCS09336 | 0.63 - 0.75 | 16 - 19    | Yellow      | 5,000                     | 2,267                   |
| ZCS09337 | 0.75 - 1.0  | 19 - 25    | Red         | 6,000                     | 2,721                   |
| ZCS09338 | 1.0 - 1.25  | 25 - 32    | Blue        | 6,000                     | 2,721                   |
| ZCS09339 | 1.25 - 1.50 | 32 - 38    | White       | 6,000                     | 2,721                   |

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Australia Pty. Ltd

## Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



**GET IN TOUCH** 



+61 3 8840 6556



sales@slingcoaustralia.com.au