


Accessories – Bore-Gard® Trenchless Raceway



Size	Locking Straps
2"	GSUP2
3"	GSUP3
4"	GSUP
5"	GSUP5
6"	GSUP6
8"	GSUP8

Rectangular Locking Strap w/No-slip Barbs and Crush Rib – made of Nylon material.


Fast, easy, secure connection. No cementing/tools required. Eliminates costly fusion welding.

Shipped installed with product - always have the right size when you need it.

Barbs prevent strap from slipping or being pulled out during installation.

Crush rib provides a frictional fit. Prevents roll-out from locking groove.

Size	Gaskets
2"	HBOR2
3"	HBOR3
4"	HBOR
5"	HBOR5
6"	HBOR6
8"	HBOR8



Factory-installed Triple-Lobed Gasket – made of Nitrile Material

Provides a watertight seal to keep out ground water and drilling fluid.

Can contain air pressure up to 80 PSI during cable installation.



Size	Pulling Eyes
2"	BG2PE
3"	BG3PE
4"	BG4PE
5"	BG5PE
6"	BG6PE
8"	BG8PE

1. Trim spigot end before attaching pulling eye.

2. Insert pulling eye into spigot end of Bore-Gard.

3. Tighten pulling eye so it expands against the interior of the conduit. Use of sleeve over O.D of conduit is recommended.

4. Installer should use appropriate Instrumentation to insure maximum pull rating is NOT exceeded.

5. Attach next stick of Bore-Gard.

Bore-Gard is shipped with caps. The end caps keep the product clean and clear from debris, making the cable/innerduct installations faster.



Markings



2" – 6" ETL
Listed to
UL651



3"-6" Schedule
40 CSA Listed



National
Electrical Code



NEMA TC-2



Bore-Gard is
Made in the
U.S.A.

Utility & Telecommunication Markets

Outdoor Horizontal Directional Drilled

- Under Roads, Highways, Airport Runways, Railways & Waterways • Metropolitan/Urban Areas • Rural Areas • or any other buried conduit application....